



HT210 Autoranging Digital Multimeter With Temperature measurement - CAT III Three Year Warranty



Features

- DC Voltage
- AC Voltage
- Resistance and continuity test with buzzer.
- Diode test
- Capacitance
- Frequency
- Duty cycle
- Temperature with type K probe
- Data HOLD
- Relative mode
- Complete autorange
- Backlight
- Auto Power OFF

STANDARD ACCESSORIES

KIT4000A : Test leads with 2mm tip

Adapter for type K probes

TK 101 Type K bead probe

Battery

Soft carry case

User manual

OPTIONAL ACCESSORIES

TK107 : Type K probe for air/gas temperature

TK108 : Type K probe for semi-solid substances temperature

TK109 : Type K probe for liquid temperature

TK110 : Type K probe for surface temperature

TK111 : Type K probe for surface temp. with 90 degree tip



RAPID-TECH EQUIPMENT
For all your Test Equipment Requirements

1800 358 531
Web www.rapid-tech.com.au
E-Mail info@rapid-tech.com.au

1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as \pm (% reading + number of dgt) at 18°C + 28°C, <70%HR

DC VOLTAGE (Autorange)

Range	Resolution	Accuracy	Overload protection
4.000V	0.001V	$\pm(1.2\%rdg+2dgt)$	600VDC/ACrms
40.00V	0.01V		
400.0V	0.1V		
600V	1V	$\pm(1.5\%rdg+2dgt)$	

Input impedance: 7.8M Ω

AC VOLTAGE (Autorange)


Range	Resolution	Accuracy (50 + 400Hz)	Overload protection
4.000V	0.001V	$\pm(1.2\%rdg+4dgt)$	600VDC/ACrms
40.00V	0.01V	$\pm(1.5\%rdg+3dgt)$	
400.0V	0.1V		
600V	1V	$\pm(2.0\%rdg+4dgt)$	

Input impedance: 7.8M Ω


RESISTANCE (Autorange)

Range	Resolution	Accuracy	Overload protection
400.0 Ω	0.1 Ω	$\pm(1.2\%rdg+4dgt)$	250VDC/ACrms
4.000k Ω	0.001k Ω	$\pm(1.0\%rdg+2dgt)$	
40.00k Ω	0.01k Ω	$\pm(1.2\%rdg+2dgt)$	
400.0k Ω	0.1k Ω		
4.000M Ω	0.001M Ω	$\pm(2.0\%rdg+3dgt)$	
40.00M Ω	0.01M Ω		

DIODE TEST

Range	Resolution	Accuracy	Open voltage	Overload protection
	1mV	$\pm(10\%rdg+5dgt)$	circa 1.5VDC	250VDC/ACrms

CONTINUITY TEST

Range	Buzzer	Test current	Overload protection
	R<150 Ω	<0.3VmA	250VDC/ACrms

FREQUENCY (Autorange)

Range	Resolution	Accuracy	Sensitivity	Overload protection
5.000Hz	0.001Hz	$\pm(1.5\%rdg+5dgt)$	>8Vrms	250VDC/ACrms
50.00Hz	0.01Hz			
500.0Hz	0.1Hz	$\pm(1.2\%rdg+3dgt)$		
5.000kHz	10Hz			
50.00kHz	10Hz			
500.0kHz	100Hz	$\pm(1.5\%rdg+4dgt)$		
5.000MHz	1kHz			
10.00MHz	10kHz			

Note: on AC Voltage the frequency range is: 10Hz +10kHz ; Sensitivity: > 15Vrms

DUTY CYCLE (Autorange)

Range	Resolution	Accuracy	Sensitivity	Overload protection
0.5 - 99%	0.1%	$\pm(1.2\%rdg + 2dgt)$	>8Vrms	250VDC/ACrms

100 μ s< pulse duration <100ms ; Frequency range: 5Hz + 150Hz

Note: on AC Voltage the frequency range is: 10Hz +10kHz ; Sensitivity: > 15Vrms



RAPID-TECH EQUIPMENT

For all your Test Equipment Requirements

1800 358 531
Web www.Rapid-tech.com.au
E-Mail info@rapid-tech.com.au

CAPACITANCE (Aurorange)

Range	Resolution	Accuracy	Overload protection
40.00nF	0.01nF	$\pm(5.0\%rdg+7dgt)$	250VDC/ACrms
400.0nF	0.1nF	$\pm(3.0\%rdg+5dgt)$	
4.000 μ F	0.001 μ F		
40.00 μ F	0.01 μ F		
100.0 μ F	0.1 μ F	$\pm(5.0\%rdg+5dgt)$	

TEMPERATURE WITH TYPE K PROBE (Aurorange)

Range	Resolution	Accuracy	Overload protection
-20°C ÷ 400°C	0.1°C	$\pm(3.0\%rdg+5^{\circ}C)$	250VDC/ACrms
400°C ÷ 760°C	1°C		
-4°F ÷ 752°F	0.1°F	$\pm(3.0\%rdg+9^{\circ}F)$	
752F ÷ 1400°F	1°F		

2. GENERAL SPECIFICATIONS

Display:

- LCD, 3 ½ dgt, 4000 points plus sign and decimal point
- Automatic polarity indication
- Backlight
- "OL" overrange indication

Features:

- HOLD
- REL
- AutoPowerOFF after 30 minutes of idleness

Low battery indication:

- "□+ -" appears when the battery voltage is low

Operating temperature:

- 0°C to 50°C, <70%HR

Storage temperature:

- -20°C to 60°C, <80%HR

General information:

- Max altitude: 2000m
- Pollution degree: 2
- Insulation: double insulation

Power supply:

- 1x9V battery NEDA 1604 IEC 6F22

Size:

- 138(L)x68(W)x37(H) mm

Weight (included battery):

- 210g



RAPID-TECH EQUIPMENT

For all your Test Equipment Requirements

1800 358 531

Web www.Rapid-tech.com.au

E-Mail info@rapid-tech.com.au