



- DC Voltage up to 100.0000 V, 20 ppm
- DC Current up to 50.0000 mA, 50 ppm
- Full accuracy in wide temperature range 23 +/- 10°C
- Rapid amplitude changes for dynamic applications
- Frequency up to 15 kHz, 50 ppm
- TC simulation R, S, B, J, T, E, K, N
- Resistance up to 300 kΩ and RTD simulation Pt, Ni (option)
- RS232 (optionally USB, IEEE488, Ethernet)

Precision DC calibrator M160 is a portable source of industrial process signals including DC voltage, DC current, thermocouple and RTD simulation, resistance and frequency. Unlike most of the other process calibrators, the M160 comes with exceptional 20 ppm accuracy over 20°C-wide reference temperature range. All these features are combined with user friendly interface multi-interface remote control and robust design make this calibrator ideal for both calibration laboratories as well as industry professionals.

Main parameters of both generated and measured signals are displayed on large LCD together with function-specific tooltip, providing auxiliary information like range, accuracy or load limit.

Instrument can be connected to different ATE systems via RS232, USB, LAN or GPIB interface.

M160 is sophisticated instrument with its own recalibration procedure. The procedure enables to correct any deviation without mechanical adjustment.

DC Voltage source accuracy

| Range / Resolution | Accuracy | Max. load |
|-----------------------|-----------------|-----------|
| 0.0000 - 300.0000 mV | 20 ppm + 3 μV | 50 mA |
| 0.000000 - 3.000000 V | 20 ppm + 20 μV | 50 mA |
| 0.00000 - 30.00000 V | 20 ppm + 200 μV | 50 mA |
| 0.0000 - 100.0000 V | 20 ppm + 1 mV | 25 mA |

Frequency meter accuracy

Summary range: 10 mHz to 100 kHz
 Frequency resolution: 5½ digits
 Accuracy: 50 ppm

DC Current source accuracy

| Range / Resolution | Accuracy | Max. load |
|---------------------|---------------|-----------|
| 0.0000 - 25.0000 mA | 50 ppm + 1 μA | 100 V |
| 0.0000 - 50.0000 mA | 50 ppm + 1 μA | 30 V |

Frequency source accuracy

| Range / Resolution | Accuracy |
|------------------------|----------|
| 10.0000 - 200.0000 mHz | 50 ppm |
| 200.001 - 2000.000 mHz | 50 ppm |
| 2.00001 - 20.00000 Hz | 50 ppm |
| 20.0001 - 200.0000 Hz | 50 ppm |
| 200.01 - 2000.00 Hz | 50 ppm |
| 2.0001 - 4.0000 kHz | 100 ppm |
| 4.001 - 10.000 kHz | 600 ppm |
| 10.01 - 15.00 kHz | 1500 ppm |

Max. load 30V/50mA or internal pull up to +5V.

TC simulation

TC types: R, S, B, J, T, E, K, N
Resolution: 0.01 °C
Accuracy: 0.1 – 0.8 °C, see user's manual for detailed specification
External RJ accuracy: 0.02 °C (option)

RTD simulation (option)

RTD types: Pt, Ni
Resolution: 0.01 °C
Accuracy: 0.1 – 0.2 °C, see user's manual for detailed specification

Real resistance decade (option)

Resistance range: 10 Ω - 300 kΩ
Resolution: from 0.0001 Ω
Accuracy: 0.02 %

General information

Reference temperature: +13 °C ... +33 °C
Operating temperature: +5 °C ... +45 °C
Storage temperature: -10 °C ... +55 °C
Remote control: RS232 interface (optionally USB, LAN, IEEE488)
Power supply: 115/230 Vac, 50/60 Hz, 60W max
Dimensions: W 390 mm, H 128 mm, D 310 mm
Weight: 5.5 kg

Content of delivery

M160 Precision DC calibrator
Cable RS 232
User's manual
Option 14 - test lead (black)
Option 15 - test lead (red)
Option 160-60 - frequency adapter (M160i)
Option 160-70 - R/frequency adapter (M160)

Ordering information – options

Bus
M160-V1xxx - RS232
M160-V2xxx - RS232, USB, LAN, GPIB

Functions
M160i-Vxxxx - U, I, TC, Frequency
M160-Vxxxx - U, I, TC, Frequency, RTD, R

Housing
M160-Vxx0x - table version
M160-Vxx1x - module 19", 3HE

Extra ordered

Option 91 - external RJ for thermocouples

Voltage

VOLTAGE 2W 16:12:06

10.0000 V

Limit 50.00 mA Adjustable
Range Auto Output 0.003 mA

Function
Settings
Preset
Menu

Temperature

RTD SIM 4W 11:35:47

Spec. 0.10 °C Min -200 °C Max 850 °C Resistance 1385.05 Ω

100.00 °C

RTD Type Platinum R0 1000 Ω
Standard PT385 (90)

Meter Frequency 0.00000 Hz

x 10
: 10
+/-
Cancel

Menu

MENU

Information about calibrator...

Information
Device
System
Interface
Calibration

Select
Exit

Recalibration

CALIBRATION 16:29:11 01.09.2016

Voltage Full range +
Range 300 mV 3 / 4

Nominal value 285 mV
Requested accuracy 5.00 μV
Last calibrated 01.15.2015

+83.6896 %

Previous
Next
History
Close