

TECHNICAL DATA

# Fluke Ti480U Ti401U Ti300U Infrared Thermal Cameras



## Key features

- It is equipped with a new sensor and optical system, the imaging effect breaks the parameter limit, the image sharpness is further improved, the target is clearer, and the problem region is presented more clearly
- UltraFocus focusing technology: effective focusing with image algorithm, it can automatically focus in 1 s according to the temperature difference in complex scenes; laser autofocus, free choice of test targets; continuous auto focus function makes inspection work easier
- Up to 30Hz frame rate, the full range of "camera motion" for smooth and free observation, video recording without frame drop or lag
- Temperature measurement range up to 1200 °C to verify higher process requirements and explore more R&D fields
- Support up to 10x digital zoom, free screen zooming, check long-distance targets: high-voltage equipment, overhead pipelines, large mechanical equipment
- SmartView IR software for PC to process thermal video, analyze data, export reports, and complete the final step of the job
- Classic industrial design: inheriting the appearance design and material of the Vision Series, it is still comfortable to hold with one hand and easy to operate, and it is not easy to fatigue for long time use

## Product overview: Fluke Ti480U Ti401U Ti300U Infrared Thermal Cameras

The Fluke Vison Series is one of the well-received thermal cameras, from Ti200, Ti300, Ti400 to Ti480Pro Series, we listen to the voice of users all the way to iterate better product performance.

With the support of the new sensor, the Vison Series now gets into a "brand new stage" and makes a substantial progress in image quality, focus speed and test functions. While retaining the classic industrial design, it improves user experience and help users with practical work.

We believe that every day engineers are making things better around them, and Fluke is also striving for this common goal together with its users.

## Specifications: Fluke Ti480U Ti401U Ti300U Infrared Thermal Cameras

Function Parameter	Fluke Ti480u	Fluke Ti401u	Fluke Ti300u
<b>Basic Parameters</b>			
IR resolution	640 × 480	640 × 480	384 × 288
SuperResolution	1280 × 960	-	-
Detector type	Uncooled focal plane infrared detector		
Thermal sensitivity (NETD) @ 30 °C	50 mk (0.05 °C)	75 mk (0.075 °C)	75 mk (0.075 °C)
Spectral response	7 to 14 μm		
Image frame rate	30 Hz	9/30 Hz	9/30 Hz
Lens Field of View (FOV)	25° x 19°		
Spatial resolution (IFOV)	0.68 mrad	0.68 mrad	1.14 mrad
Minimum imaging distance	0.25 m		0.1 m
Lens focal distance	f 24.8		f 15
Focus	Auto / Manual Focus		
Lens recognition	Auto		
Optional lens	2x telephoto lens		
	4x telephoto lens		
	Wide-angle lens		
Digital Zoom	1-10x	1-10x	1-4x
<b>Measurement Analysis</b>			
Temperature range	-20 °C to 1200 °C	-20 °C to 650 °C	

Temperature measurement range	-20 °C to 120 °C	-20 °C to 120 °C	
	0 °C to 650 °C	0 °C to 650 °C	
	300 °C to 1200 °C		
Intelligent range	Yes	Yes	Yes
Temperature accuracy	±2 °C or 2%, whichever is greater (@ 23 °C ± 5 °C ambient temperature)		
Temperature measurement area	Spots: 16		
	Lines: 8		
	Areas: 12		
Global temperature measurement correction	Support emissivity, environment temperature, reflected temperature, relative humidity, temperature measurement distance, IR window (temperature and transmittance) correction		
Area temperature measurement correction	Yes		
Area audible alarm	Support high and low temperature alarm for the highest, lowest and average temperature of the area		
Temperature rise function	Reference temperature can be the highest, lowest, average or custom temperature of the area		
On-Imager analysis	The thermal photos or videos are directly analyzed in the Imager		
Analysis software for PC	SmartView IR		
<b>Image Display</b>			
Display Screen	3.5" LCD, 640 × 480		
Image mode	Thermal image, visible image, PIP		
Palettes	Grey, Iron 10, IronRed, Rainbow, Grey10, GreyRed, MidGrey, Yellow and Rain		
	Palettes can be inverted		
	Support real-time palette preview and switching		
Temperature span mode	Support automatic adjustment of temperature span (min. 3 °C)		
	Support manual adjustment of temperature span (min. 2 °C)		
	The maximum and minimum value of temperature span can be selected by touch (min. 2 °C)		
Color and audible alarm	Yes. Above the temperature, below the temperature and between the temperature		
Information displayed on the image	Display the global maximum, minimum, average temperature and temperature measurement parameters		
High/low temperature tracking	Marking and automatically tracks high and low temperature points		
<b>IR-Fusion</b>			
Blending degree of a visual photo and an infrared thermal image	0% to 100%		
Picture-in-Picture (PIP)	Yes. The size, position and blending degree of infrared window can be adjusted.		
<b>Shooting Function</b>			
Digital camera	Industrial grade digital camera with 13-megapixel lens		

Memory card	Micro SD card, standard 32 GB; expandable to 64 GB, 128 GB		
Shooting Mode	Support single frame and time-lapse shooting		
Image format	.bmp .jpg		
Screen freeze	Support single frame shooting and fully-radiometric video recording	Support single frame shooting	Support single frame shooting and fully-radiometric video recording
Code scanning function	Yes. A QR code and barcode can be scanned as a label		
Annotation function	Support voice, text and label annotation		
IR-PhotoNotes	5 images	2 images	2 images
Fully-radiometric video recording	Support thermal video recording for analysis	-	Support thermal video recording for analysis
Non-fully-radiometric video recording	Support thermal video, visible video recording (only for viewing, not for analysis)	-	Support thermal video, visible video recording (only for viewing, not for analysis)
Video frame rate	1 Hz to 9/16 Hz	-	1 Hz to 9/16 Hz
Video Format	.is5, .mp4	-	.is5, .mp4
Gallery	Support viewing, editing and deleting captured thermal images and video files		
<b>Data Connection</b>			
Bluetooth connection	Support BT4.2 LE		
USB interface	Type-A, USB 2.0		
HDMI interface	Mini HDMI interface, HDMI 1.4		
Fully-radiometric video analysis via PC software	Fully-radiometric video analysis via PC software		
Remote display via software	Yes	-	-
Remote operation via software	Yes	-	Yes
HDMI output	Support connection to a display or a projector via the HDMI interface		
<b>Ancillary Function</b>			
Laser	Yes		
Temperature feature measurement	Support measuring the length of the temperature measurement line; support measuring the rectangular and circular area of the temperature measurement area		
LED torch/flashlight	Support flashlight and flash mode		
<b>Power System</b>			
Battery type	7.2V, 19Whr lithium battery, replaceable and rechargeable on field		
Battery life	2 to 3 hours/battery (*Actual life depends on settings and usage)		
Charge Mode	10-15 V DC charging		
Charging time	2.5 hours to full charge		
Energy saving management	Auto screen-off		

Battery charge	Ti SBC3B Two Bay Battery Charger (100 V ac to 240 V ac, 50/60 Hz, included), or in-Imager charging. Optional 12 V automotive charging adapter.	
External power supply	Power adapter (110 to 220 V, 50/60 Hz AC power)	
<b>Reliability and Certification</b>		
Safety standard	IEC 61010-1: pollution degree 2	
Electromagnetic Compatibility (EMC)	International: IEC 61326-1: Industrial Electromagnetic Environment; CISPR 11: Group 1, Class A Korea (KCC): Class A Equipment (Industrial Broadcasting & Communication Equipment)	
Radio frequency	2400 MHz to 2483.5 MHz	
Radio output power	<100 mW	
Laser	IEC 60825-1, Class 2; 650 nm; <1 mW	
Ingress protection rating	IEC 60529: IP52	
Drop test	Designed for 1 m drop resistance	
<b>Physical Parameter</b>		
Operating temperature	-10 °C to 50 °C	
Storage temperature	-20 °C to 50 °C, without battery	
Relative humidity	0% to 95% (non-condensing)	
Dimensions	27.9 cm x 12.2 cm x 17.5 cm	
Weight	1215 g	1188 g
<b>Warranty and Maintenance</b>		
Warranty	2 years	
Recommended calibration period	2 years	
<b>Supported Languages</b>		
Supported languages	Simplified Chinese, English, Japanese, Korean, Traditional Chinese	
<b>Optional Lenses</b>		
Lens name	Field of view	Minimum imaging distance
Standard lens	25° x 19°	0.1 m
Wide-angle lens	44° x 34°	0.1 m
2x telephoto lens	12° x 9°	1.0 m (Ti480U / Ti401U) 0.25 m (Ti300U)
4x telephoto lens	7° x 5°	1.0 m (Ti480U / Ti401U) 0.25 m (Ti300U)

## Ordering information



### Fluke Ti480U

---

Fluke Ti480U  
Thermal Cameras

- The Fluke Ti480U Thermal Camera
- Charger
- Battery
- Hard carrying case
- HDMI cable
- USB cable
- Safety information
- Report

### Fluke Ti401U

---

Fluke Ti401U  
Thermal Cameras

- The Fluke Ti401U Thermal Camera
- Charger
- Battery
- Carrying case
- HDMI cable
- USB cable
- Safety information
- Report

## Fluke Ti300U

---

Fluke Ti300U

Thermal Cameras

- The Fluke Ti300U Thermal Camera
  - Charger
  - Battery
  - Carrying case
  - HDMI cable
  - USB cable
  - Safety information
  - Report
-

**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**Fluke Australia**  
Unit 26, 7 Anella Ave  
Castle Hill, NSW 2154 Australia  
Phone: 61 2 8850-3333  
[www.fluke.com.au](http://www.fluke.com.au)

©2023 Fluke Corporation. All rights reserved.  
Specifications subject to change without notice.  
07/2023

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**